

DRILL PIPE INSPECTION SUMMARY

Date: 11/12/2025 to 11/12/2025

Customer		Inspected at	Lead NDT Yard			
Rig Name	N/A	Inspection Unit	01			
Well Location	N/A	Job Spec	DS-1 WORKSTRINGS / API RP 7G			
Customer Order #	N/A	Inspected by	1	Blake	3	Aaron
			2	Matt	4	Helpers

	Inches		Inches		Inches	Manufacturing Dates		
Pipe Size	2 7/8	New O.D.	3 3/8	Max. Ctbr. Dia.	1	1		10
Weight	7.90	Min. O.D.	3 5/16	Min. Ctbr. Len.	1	2		11
Grade	P-110	Min. I.D.	2 15/16	Min. Box Len.	1.000	3		12
Connection	PH-6	Min. Shdr. Width	1	Max. Box Len.	1.000	4		13
Range	0.276	Min. Seal Width	1	Min. Box TS	3	5		14
Nom. Wall	0.248	Bevel Diameter	1	Min. Pin Len.	1.000	6		15
90% Wall	0.223			Max. Pin Len.	1.000	7		16
80% Wall	0.198			Min. Pin TS	5/16	8		17
70% Wall	0.174					9		18

TOTAL JOINTS INSPECTED 185

TUBES & TOOL JOINTS				
Tubes		Downgraded Tool Joints		Downgraded Joints' SNs
Premium	185	Pins		
Yellow		Boxes		
Orange				
Red				
Total downgraded joints (Final Class)				

MACHINE SHOP REPAIRS					
Connections		Crooked		Hardbands	
Pins		Joints		Pins	
Boxes				Boxes	
TOTALS					

WORK READY JOINTS 185
JOINTS NEEDING MACHINE SHOP REPAIR 0
DOWNGRADED JOINTS (NOT TO BE USED) 0

COMMENTS:

JOINTS 0-12.5% REMAINING WALL 1 WHITE BAND
JOINTS 12.5% TO 15% REMAINING WALL 1 YELLOW BAND

Pin Reface			
Box Reface			
W A L L	90-100%		181/(97%)
	80-89%		4/(2%)
	70-79%		0/(0%)
	Below 70%		0/(0%)



Date:	11/12/2025	-	11/12/2025	Rig Name:	N/A	Size:	2 7/8	Weight:	7.90	Nom. Wall:	0.248
Customer:				Inspected At:	Lead NDT Yard	Grade:	P-110	Connection:	PH-6	80% Wall:	0.198
Customer Order #:	N/A			Job Spec:	DS-1 WORKSTRINGS / API RP 7G	Range:	0.276	EMI Unit:	01	70% Wall:	0.174

CONNECTION DIMENSIONAL DATA CRITERIA											
PIN DIMENSIONS						BOX DIMENSIONS					
PIN LENGTH:	1.000	-	1.000	BEVEL DIAMETER:	1	BOX LENGTH:	1.000	-	1.000	C-BORE LENGTH:	1
MIN. O.D.:	3 5/16			PIN I.D.:	2 15/16	MIN. O.D.:	3 5/16			C-BORE DIAMETER:	1
MIN. SHDR. WIDTH:	1			MIN. TONG SPACE:	5/16	MIN. SHDR. WIDTH:	1			MIN. TONG SPACE:	3

JOINT NO.	SERIAL NO.	TUBE CONDITION											PIN CONDITION						BOX CONDITION						FINAL CLASS	COMMENTS	
		DENTS/MASH	SLIP AREA	CUTS/GOUGES	O.D. WEAR	PITTING	CRACKED	COATING	CROOKED	MIN. WALL THICKNESS	MAX. WALL THICKNESS	CLASS	HARDBAND	CONNECTION CLASS	REFACE	O.D.	I.D.	TONG SPACE	PIN LENGTH	HARDBAND	CONNECTION CLASS	REFACE	O.D.	TONG SPACE			BOX LENGTH
1	N/A	☐	☐	☐	☐	☐	☐	☐	☐	0.296		P	☐	OK	☐	3 3/8	2 5/16	3 3/8	1.000	☐	OK	☐	3 3/8	6 1/8	1.000	P	OK
2	N/A	☐	☐	☐	☐	☐	☐	☐	☐	0.275		P	☐	OK	☐	3 3/8	2 5/16	3 1/4	1.000	☐	OK	☐	3 3/8	6 1/4	1.000	P	OK
3	N/A	☐	☐	☐	☐	☐	☐	☐	☐	0.274		P	☐	OK	☐	3 3/8	2 5/16	5 3/16	1.000	☐	OK	☐	3 3/8	6 1/4	1.000	P	OK
4	N/A	☐	☐	☐	☐	☐	☐	☐	☐	0.310		P	☐	OK	☐	3 3/8	2 5/16	3 1/4	1.000	☐	OK	☐	3 3/8	6 1/4	1.000	P	OK
5	N/A	☐	☐	☐	☐	☐	☐	☐	☐	0.277		P	☐	OK	☐	3 3/8	2 5/16	3 1/4	1.000	☐	OK	☐	3 3/8	6	1.000	P	OK
6	N/A	☐	☐	☐	☐	☐	☐	☐	☐	0.280		P	☐	OK	☐	3 3/8	2 5/16	3 1/4	1.000	☐	OK	☐	3 3/8	6 1/4	1.000	P	OK
7	N/A	☐	☐	☐	☐	☐	☐	☐	☐	0.271		P	☐	OK	☐	3 3/8	2 5/16	1 7/8	1.000	☐	OK	☐	3 3/8	6	1.000	P	OK
8	N/A	☐	☐	☐	☐	☐	☐	☐	☐	0.269		P	☐	OK	☐	3 3/8	2 5/16	3 1/4	1.000	☐	OK	☐	3 3/8	6 1/4	1.000	P	OK
9	N/A	☐	☐	☐	☐	☐	☐	☐	☐	0.258		P	☐	OK	☐	3 3/8	2 5/16	3 1/4	1.000	☐	OK	☐	3 3/8	6 1/4	1.000	P	OK
10	N/A	☐	☐	☐	☐	☐	☐	☐	☐	0.276		P	☐	OK	☐	3 3/8	2 5/16	3 1/4	1.000	☐	OK	☐	3 3/8	6 1/4	1.000	P	OK
11	N/A	☐	☐	☐	☐	☐	☐	☐	☐	0.285		P	☐	OK	☐	3 3/8	2 5/16	3 1/4	1.000	☐	OK	☐	3 3/8	6	1.000	P	OK
12	N/A	☐	☐	☐	☐	☐	☐	☐	☐	0.283		P	☐	OK	☐	3 3/8	2 5/16	1 7/8	1.000	☐	OK	☐	3 3/8	5	1.000	P	OK
13	N/A	☐	☐	☐	☐	☐	☐	☐	☐	0.271		P	☐	OK	☐	3 3/8	2 5/16	3 1/8	1.000	☐	OK	☐	3 3/8	6 1/4	1.000	P	OK
14	N/A	☐	☐	☐	☐	☐	☐	☐	☐	0.265		P	☐	OK	☐	3 3/8	2 5/16	5 7/8	1.000	☐	OK	☐	3 3/8	8	1.000	P	OK
15	N/A	☐	☐	☐	☐	☐	☐	☐	☐	0.231		P	☐	OK	☐	3 3/8	2 5/16	5 3/8	1.000	☐	OK	☐	3 3/8	8	1.000	P	OK
16	N/A	☐	☐	☐	☐	☐	☐	☐	☐	0.283		P	☐	OK	☐	3 3/8	2 5/16	3	1.000	☐	OK	☐	3 3/8	6 1/4	1.000	P	OK
17	N/A	☐	☐	☐	☐	☐	☐	☐	☐	0.278		P	☐	OK	☐	3 3/8	2 5/16	3 1/4	1.000	☐	OK	☐	3 3/8	6	1.000	P	OK
18	N/A	☐	☐	☐	☐	☐	☐	☐	☐	0.259		P	☐	OK	☐	3 3/8	2 5/16	3	1.000	☐	OK	☐	3 3/8	6	1.000	P	OK
19	N/A	☐	☐	☐	☐	☐	☐	☐	☐	0.250		P	☐	OK	☐	3 3/8	2 5/16	3 1/4	1.000	☐	OK	☐	3 3/8	6 1/4	1.000	P	OK
20	N/A	☐	☐	☐	☐	☐	☐	☐	☐	0.262		P	☐	OK	☐	3 3/8	2 5/16	3 1/2	1.000	☐	OK	☐	3 3/8	6 1/4	1.000	P	OK



Date:	11/12/2025	-	11/12/2025	Rig Name:	N/A	Size:	2 7/8	Weight:	7.90	Nom. Wall:	0.248
Customer:	SCOTCO			Inspected At:	Lead NDT Yard	Grade:	P-110	Connection:	PH-6	80% Wall:	0.198
Customer Order #:	N/A			Job Spec:	DS-1 WORKSTRINGS / API RP 7G	Range:	0.276	EMI Unit:	01	70% Wall:	0.174

CONNECTION DIMENSIONAL DATA CRITERIA																	
PIN DIMENSIONS						BOX DIMENSIONS											
PIN LENGTH:	1.000		-	1.000		BEVEL DIAMETER:	1		BOX LENGTH:	1.000		-	1.000		C-BORE LENGTH:	1	
MIN. O.D.:	3 5/16				PIN I.D.:	2 15/16		MIN. O.D.:	3 5/16				C-BORE DIAMETER:	1			
MIN. SHDR. WIDTH:	1				MIN. TONG SPACE:	5/16		MIN. SHDR. WIDTH:	1				MIN. TONG SPACE:	3			

JOINT NO.	SERIAL NO.	TUBE CONDITION											PIN CONDITION							BOX CONDITION						FINAL CLASS	COMMENTS	
		DENTS/MASH	SLIP AREA	CUTS/GOUGES	O.D. WEAR	PITTING	CRACKED	COATING	CROOKED	MIN. WALL THICKNESS	MAX. WALL THICKNESS	CLASS	HARDBAND	CONNECTION CLASS	REFACE	O.D.	I.D.	TONG SPACE	PIN LENGTH	HARDBAND	CONNECTION CLASS	REFACE	O.D.	TONG SPACE	BOX LENGTH			
21	N/A	☐	☐	☐	☐	☐	☐	☐	☐	0.278		P	☐	OK	☐	3 3/8	2 5/16	3 1/4	1.000	☐	OK	☐	3 3/8	5 1/2	1.000	P	OK	
22	N/A	☐	☐	☐	☐	☐	☐	☐	☐	0.288		P	☐	OK	☐	3 3/8	2 5/16	3 1/4	1.000	☐	OK	☐	3 3/8	6 1/4	1.000	P	OK	
23	N/A	☐	☐	☐	☐	☐	☐	☐	☐	0.261		P	☐	OK	☐	3 3/8	2 5/16	3 1/4	1.000	☐	OK	☐	3 3/8	6 1/4	1.000	P	OK	
24	N/A	☐	☐	☐	☐	☐	☐	☐	☐	0.280		P	☐	OK	☐	3 3/8	2 5/16	3	1.000	☐	OK	☐	3 3/8	3 1/2	1.000	P	OK	
25	N/A	☐	☐	☐	☐	☐	☐	☐	☐	0.270		P	☐	OK	☐	3 3/8	2 5/16	3 1/4	1.000	☐	OK	☐	3 3/8	6	1.000	P	OK	
26	N/A	☐	☐	☐	☐	☐	☐	☐	☐	0.263		P	☐	OK	☐	3 3/8	2 5/16	3 1/4	1.000	☐	OK	☐	3 3/8	5	1.000	P	OK	
27	N/A	☐	☐	☐	☐	☐	☐	☐	☐	0.258		P	☐	OK	☐	3 3/8	2 5/16	3 1/4	1.000	☐	OK	☐	3 3/8	6 1/4	1.000	P	OK	
28	N/A	☐	☐	☐	☐	☐	☐	☐	☐	0.254		P	☐	OK	☐	3 3/8	2 5/16	3 1/4	1.000	☐	OK	☐	3 3/8	6 1/4	1.000	P	OK	
29	N/A	☐	☐	☐	☐	☐	☐	☐	☐	0.269		P	☐	OK	☐	3 3/8	2 5/16	3 3/8	1.000	☐	OK	☐	3 3/8	6	1.000	P	OK	
30	N/A	☐	☐	☐	☐	☐	☐	☐	☐	0.236		P	☐	OK	☐	3 3/8	2 5/16	3	1.000	☐	OK	☐	3 3/8	6	1.000	P	OK	
31	N/A	☐	☐	☐	☐	☐	☐	☐	☐	0.266		P	☐	OK	☐	3 3/8	2 5/16	3	1.000	☐	OK	☐	3 3/8	8 1/4	1.000	P	OK	
32	N/A	☐	☐	☐	☐	☐	☐	☐	☐	0.272		P	☐	OK	☐	3 3/8	2 5/16	3 1/4	1.000	☐	OK	☐	3 3/8	6 1/4	1.000	P	OK	
33	N/A	☐	☐	☐	☐	☐	☐	☐	☐	0.244		P	☐	OK	☐	3 3/8	2 5/16	3 1/4	1.000	☐	OK	☐	3 3/8	6 1/4	1.000	P	OK	
34	N/A	☐	☐	☐	☐	☐	☐	☐	☐	0.278		P	☐	OK	☐	3 3/8	2 5/16	2 1/2	1.000	☐	OK	☐	3 3/8	6 1/4	1.000	P	OK	
35	N/A	☐	☐	☐	☐	☐	☐	☐	☐	0.266		P	☐	OK	☐	3 3/8	2 5/16	3	1.000	☐	OK	☐	3 3/8	6 1/4	1.000	P	OK	
36	N/A	☐	☐	☐	☐	☐	☐	☐	☐	0.269		P	☐	OK	☐	3 3/8	2 5/16	5 1/4	1.000	☐	OK	☐	3 3/8	6	1.000	P	OK	
37	N/A	☐	☐	☐	☐	☐	☐	☐	☐	0.262		P	☐	OK	☐	3 3/8	2 5/16	3 1/8	1.000	☐	OK	☐	3 3/8	6 1/4	1.000	P	OK	
38	N/A	☐	☐	☐	☐	☐	☐	☐	☐	0.236		P	☐	OK	☐	3 3/8	2 5/16	3 1/4	1.000	☐	OK	☐	3 3/8	6	1.000	P	OK	
39	N/A	☐	☐	☐	☐	☐	☐	☐	☐	0.269		P	☐	OK	☐	3 3/8	2 5/16	3 1/2	1.000	☐	OK	☐	3 3/8	5	1.000	P	OK	
40	N/A	☐	☐	☐	☐	☐	☐	☐	☐	0.274		P	☐	OK	☐	3 3/8	2 5/16	3 1/4	1.000	☐	OK	☐	3 3/8	6	1.000	P	OK	



Date:	11/12/2025	-	11/12/2025	Rig Name:	N/A	Size:	2 7/8	Weight:	7.90	Nom. Wall:	0.248
Customer:				Inspected At:	Lead NDT Yard	Grade:	P-110	Connection:	PH-6	80% Wall:	0.198
Customer Order #:	N/A			Job Spec:	DS-1 WORKSTRINGS / API RP 7G	Range:	0.276	EMI Unit:	01	70% Wall:	0.174

CONNECTION DIMENSIONAL DATA CRITERIA											
PIN DIMENSIONS						BOX DIMENSIONS					
PIN LENGTH:	1.000	-	1.000	BEVEL DIAMETER:	1	BOX LENGTH:	1.000	-	1.000	C-BORE LENGTH:	1
MIN. O.D.:	3 5/16			PIN I.D.:	2 15/16	MIN. O.D.:	3 5/16			C-BORE DIAMETER:	1
MIN. SHDR. WIDTH:	1			MIN. TONG SPACE:	5/16	MIN. SHDR. WIDTH:	1			MIN. TONG SPACE:	3

JOINT NO.	SERIAL NO.	TUBE CONDITION											PIN CONDITION							BOX CONDITION						FINAL CLASS	COMMENTS
		DENTS/MASH	SLIP AREA	CUTS/GOUGES	O.D. WEAR	PITTING	CRACKED	COATING	CROOKED	MIN. WALL THICKNESS	MAX. WALL THICKNESS	CLASS	HARBAND	CONNECTION CLASS	REFACE	O.D.	I.D.	TONG SPACE	PIN LENGTH	HARBAND	CONNECTION CLASS	REFACE	O.D.	TONG SPACE	BOX LENGTH		
41	N/A	☐	☐	☐	☐	☐	☐	☐	☐	0.270		P	☐	OK	☐	3 3/8	2 5/16	3 5/16	1.000	☐	OK	☐	3 3/8	6	1.000	P	OK
42	N/A	☐	☐	☐	☐	☐	☐	☐	☐	0.241		P	☐	OK	☐	3 3/8	2 5/16	3 1/4	1.000	☐	OK	☐	3 3/8	6 1/4	1.000	P	OK
43	N/A	☐	☐	☐	☐	☐	☐	☐	☐	0.239		P	☐	OK	☐	3 3/8	2 5/16	3 1/4	1.000	☐	OK	☐	3 3/8	6 1/4	1.000	P	OK
44	N/A	☐	☐	☐	☐	☐	☐	☐	☐	0.275		P	☐	OK	☐	3 3/8	2 5/16	5	1.000	☐	OK	☐	3 3/8	8 1/8	1.000	P	OK
45	N/A	☐	☐	☐	☐	☐	☐	☐	☐	0.264		P	☐	OK	☐	3 3/8	2 5/16	3 1/8	1.000	☐	OK	☐	3 3/8	6	1.000	P	OK
46	N/A	☐	☐	☐	☐	☐	☐	☐	☐	0.280		P	☐	OK	☐	3 3/8	2 5/16	3 1/4	1.000	☐	OK	☐	3 3/8	6	1.000	P	OK
47	N/A	☐	☐	☐	☐	☐	☐	☐	☐	0.278		P	☐	OK	☐	3 3/8	2 5/16	3 1/4	1.000	☐	OK	☐	3 3/8	6	1.000	P	OK
48	N/A	☐	☐	☐	☐	☐	☐	☐	☐	0.251		P	☐	OK	☐	3 3/8	2 5/16	3 3/8	1.000	☐	OK	☐	3 3/8	6	1.000	P	OK
49	N/A	☐	☐	☐	☐	☐	☐	☐	☐	0.270		P	☐	OK	☐	3 3/8	2 5/16	3 1/2	1.000	☐	OK	☐	3 3/8	6 1/8	1.000	P	OK
50	N/A	☐	☐	☐	☐	☐	☐	☐	☐	0.288		P	☐	OK	☐	3 3/8	2 5/16	3 1/4	1.000	☐	OK	☐	3 3/8	4 7/8	1.000	P	OK
51	N/A	☐	☐	☐	☐	☐	☐	☐	☐	0.266		P	☐	OK	☐	3 3/8	2 5/16	3 3/8	1.000	☐	OK	☐	3 3/8	6 1/8	1.000	P	OK
52	N/A	☐	☐	☐	☐	☐	☐	☐	☐	0.273		P	☐	OK	☐	3 3/8	2 5/16	1 7/8	1.000	☐	OK	☐	3 3/8	6 1/8	1.000	P	OK
53	N/A	☐	☐	☐	☐	☐	☐	☐	☐	0.263		P	☐	OK	☐	3 3/8	2 5/16	3 1/4	1.000	☐	OK	☐	3 3/8	6	1.000	P	OK
54	N/A	☐	☐	☐	☐	☐	☐	☐	☐	0.278		P	☐	OK	☐	3 3/8	2 5/16	3 1/4	1.000	☐	OK	☐	3 3/8	4 3/4	1.000	P	OK
55	N/A	☐	☐	☐	☐	☐	☐	☐	☐	0.283		P	☐	OK	☐	3 3/8	2 5/16	3 3/8	1.000	☐	OK	☐	3 3/8	6 1/8	1.000	P	OK
56	N/A	☐	☐	☐	☐	☐	☐	☐	☐	0.261		P	☐	OK	☐	3 3/8	2 5/16	3 1/8	1.000	☐	OK	☐	3 3/8	6 1/4	1.000	P	OK
57	N/A	☐	☐	☐	☐	☐	☐	☐	☐	0.261		P	☐	OK	☐	3 3/8	2 5/16	3 3/8	1.000	☐	OK	☐	3 3/8	6 1/4	1.000	P	OK
58	N/A	☐	☐	☐	☐	☐	☐	☐	☐	0.280		P	☐	OK	☐	3 3/8	2 5/16	3 1/4	1.000	☐	OK	☐	3 3/8	4 3/4	1.000	P	OK
59	N/A	☐	☐	☐	☐	☐	☐	☐	☐	0.243		P	☐	OK	☐	3 3/8	2 5/16	5 1/4	1.000	☐	OK	☐	3 3/8	7	1.000	P	OK
60	N/A	☐	☐	☐	☐	☐	☐	☐	☐	0.266		P	☐	OK	☐	3 3/8	2 5/16	3 1/16	1.000	☐	OK	☐	3 3/8	6 1/8	1.000	P	OK



Date:	11/12/2025	-	11/12/2025	Rig Name:	N/A	Size:	2 7/8	Weight:	7.90	Nom. Wall:	0.248
Customer:				Inspected At:	Lead NDT Yard	Grade:	P-110	Connection:	PH-6	80% Wall:	0.198
Customer Order #:	N/A			Job Spec:	DS-1 WORKSTRINGS / API RP 7G	Range:	0.276	EMI Unit:	01	70% Wall:	0.174

CONNECTION DIMENSIONAL DATA CRITERIA											
PIN DIMENSIONS						BOX DIMENSIONS					
PIN LENGTH:	1.000	-	1.000	BEVEL DIAMETER:	1	BOX LENGTH:	1.000	-	1.000	C-BORE LENGTH:	1
MIN. O.D.:	3 5/16			PIN I.D.:	2 15/16	MIN. O.D.:	3 5/16			C-BORE DIAMETER:	1
MIN. SHDR. WIDTH:	1			MIN. TONG SPACE:	5/16	MIN. SHDR. WIDTH:	1			MIN. TONG SPACE:	3

JOINT NO.	SERIAL NO.	TUBE CONDITION											PIN CONDITION							BOX CONDITION						FINAL CLASS	COMMENTS
		DENTS/MASH	SLIP AREA	CUTS/GOUGES	O.D. WEAR	PITTING	CRACKED	COATING	CROOKED	MIN. WALL THICKNESS	MAX. WALL THICKNESS	CLASS	HARBAND	CONNECTION CLASS	REFACE	O.D.	I.D.	TONG SPACE	PIN LENGTH	HARBAND	CONNECTION CLASS	REFACE	O.D.	TONG SPACE	BOX LENGTH		
61	N/A	☐	☐	☐	☐	☐	☐	☐	☐	0.276		P	☐	OK	☐	3 3/8	2 5/16	3	1.000	☐	OK	☐	3 3/8	6 5/16	1.000	P	OK
62	N/A	☐	☐	☐	☐	☐	☐	☐	☐	0.260		P	☐	OK	☐	3 3/8	2 5/16	5 1/8	1.000	☐	OK	☐	3 3/8	6 1/4	1.000	P	OK
63	N/A	☐	☐	☐	☐	☐	☐	☐	☐	0.253		P	☐	OK	☐	3 3/8	2 5/16	3 3/8	1.000	☐	OK	☐	3 3/8	5	1.000	P	OK
64	N/A	☐	☐	☐	☐	☐	☐	☐	☐	0.254		P	☐	OK	☐	3 3/8	2 5/16	3 1/4	1.000	☐	OK	☐	3 3/8	8	1.000	P	OK
65	N/A	☐	☐	☐	☐	☐	☐	☐	☐	0.286		P	☐	OK	☐	3 3/8	2 5/16	3	1.000	☐	OK	☐	3 3/8	6	1.000	P	OK
66	N/A	☐	☐	☐	☐	☐	☐	☐	☐	0.255		P	☐	OK	☐	3 3/8	2 5/16	3 1/8	1.000	☐	OK	☐	3 3/8	5	1.000	P	OK
67	N/A	☐	☐	☐	☐	☐	☐	☐	☐	0.254		P	☐	OK	☐	3 3/8	2 5/16	5	1.000	☐	OK	☐	3 3/8	6 5/8	1.000	P	OK
68	N/A	☐	☐	☐	☐	☐	☐	☐	☐	0.296		P	☐	OK	☐	3 3/8	2 5/16	3 1/4	1.000	☐	OK	☐	3 3/8	6	1.000	P	OK
69	N/A	☐	☐	☐	☐	☐	☐	☐	☐	0.264		P	☐	OK	☐	3 3/8	2 5/16	5 3/8	1.000	☐	OK	☐	3 3/8	8	1.000	P	OK
70	N/A	☐	☐	☐	☐	☐	☐	☐	☐	0.276		P	☐	OK	☐	3 3/8	2 5/16	3 1/8	1.000	☐	OK	☐	3 3/8	6	1.000	P	OK
71	N/A	☐	☐	☐	☐	☐	☐	☐	☐	0.253		P	☐	OK	☐	3 3/8	2 5/16	3 1/4	1.000	☐	OK	☐	3 3/8	6 1/4	1.000	P	OK
72	N/A	☐	☐	☐	☐	☐	☐	☐	☐	0.240		P	☐	OK	☐	3 3/8	2 5/16	5 1/4	1.000	☐	OK	☐	3 3/8	8 1/8	1.000	P	OK
73	N/A	☐	☐	☐	☐	☐	☐	☐	☐	0.254		P	☐	OK	☐	3 3/8	2 5/16	3 3/8	1.000	☐	OK	☐	3 3/8	6 1/4	1.000	P	OK
74	N/A	☐	☐	☐	☐	☐	☐	☐	☐	0.276		P	☐	OK	☐	3 3/8	2 5/16	3 1/4	1.000	☐	OK	☐	3 3/8	6	1.000	P	OK
75	N/A	☐	☐	☐	☐	☐	☐	☐	☐	0.269		P	☐	OK	☐	3 3/8	2 5/16	5 3/8	1.000	☐	OK	☐	3 3/8	7	1.000	P	OK
76	N/A	☐	☐	☐	☐	☐	☐	☐	☐	0.270		P	☐	OK	☐	3 3/8	2 5/16	3 1/8	1.000	☐	OK	☐	3 3/8	6	1.000	P	OK
77	N/A	☐	☐	☐	☐	☐	☐	☐	☐	0.265		P	☐	OK	☐	3 3/8	2 5/16	5 3/8	1.000	☐	OK	☐	3 3/8	8	1.000	P	OK
78	N/A	☐	☐	☐	☐	☐	☐	☐	☐	0.236		P	☐	OK	☐	3 3/8	2 5/16	3 3/8	1.000	☐	OK	☐	3 3/8	6	1.000	P	OK
79	N/A	☐	☐	☐	☐	☐	☐	☐	☐	0.274		P	☐	OK	☐	3 3/8	2 5/16	3 1/8	1.000	☐	OK	☐	3 3/8	5	1.000	P	OK
80	N/A	☐	☐	☐	☐	☐	☐	☐	☐	0.269		P	☐	OK	☐	3 3/8	2 5/16	1 7/8	1.000	☐	OK	☐	3 3/8	4 1/2	1.000	P	OK



Date:	11/12/2025	-	11/12/2025	Rig Name:	N/A	Size:	2 7/8	Weight:	7.90	Nom. Wall:	0.248
Customer:				Inspected At:	Lead NDT Yard	Grade:	P-110	Connection:	PH-6	80% Wall:	0.198
Customer Order #:	N/A			Job Spec:	DS-1 WORKSTRINGS / API RP 7G	Range:	0.276	EMI Unit:	01	70% Wall:	0.174

CONNECTION DIMENSIONAL DATA CRITERIA											
PIN DIMENSIONS						BOX DIMENSIONS					
PIN LENGTH:	1.000	-	1.000	BEVEL DIAMETER:	1	BOX LENGTH:	1.000	-	1.000	C-BORE LENGTH:	1
MIN. O.D.:	3 5/16			PIN I.D.:	2 15/16	MIN. O.D.:	3 5/16			C-BORE DIAMETER:	1
MIN. SHDR. WIDTH:	1			MIN. TONG SPACE:	5/16	MIN. SHDR. WIDTH:	1			MIN. TONG SPACE:	3

JOINT NO.	SERIAL NO.	TUBE CONDITION											PIN CONDITION						BOX CONDITION						FINAL CLASS	COMMENTS	
		DENTS/MASH	SLIP AREA	CUTS/GOUGES	O.D. WEAR	PITTING	CRACKED	COATING	CROOKED	MIN. WALL THICKNESS	MAX. WALL THICKNESS	CLASS	HARDBAND	CONNECTION CLASS	REFACE	O.D.	I.D.	TONG SPACE	PIN LENGTH	HARDBAND	CONNECTION CLASS	REFACE	O.D.	TONG SPACE			BOX LENGTH
81	N/A	☐	☐	☐	☐	☐	☐	☐	☐	0.260		P	☐	OK	☐	3 3/8	2 5/16	5 1/4	1.000	☐	OK	☐	3 3/8	8	1.000	P	OK
82	N/A	☐	☐	☐	☐	☐	☐	☐	☐	0.266		P	☐	OK	☐	3 3/8	2 5/16	3 1/4	1.000	☐	OK	☐	3 3/8	6	1.000	P	OK
83	N/A	☐	☐	☐	☐	☐	☐	☐	☐	0.265		P	☐	OK	☐	3 3/8	2 5/16	3 1/4	1.000	☐	OK	☐	3 3/8	6	1.000	P	OK
84	N/A	☐	☐	☐	☐	☐	☐	☐	☐	0.265		P	☐	OK	☐	3 3/8	2 5/16	3 1/2	1.000	☐	OK	☐	3 3/8	6	1.000	P	OK
85	N/A	☐	☐	☐	☐	☐	☐	☐	☐	0.215		P	☐	OK	☐	3 3/8	2 5/16	5/8	1.000	☐	OK	☐	3 3/8	5 1/8	1.000	P	OK
86	N/A	☐	☐	☐	☐	☐	☐	☐	☐	0.275		P	☐	OK	☐	3 3/8	2 5/16	5 3/8	1.000	☐	OK	☐	3 3/8	8	1.000	P	OK
87	N/A	☐	☐	☐	☐	☐	☐	☐	☐	0.263		P	☐	OK	☐	3 3/8	2 5/16	3 1/4	1.000	☐	OK	☐	3 3/8	6 1/4	1.000	P	OK
88	N/A	☐	☐	☐	☐	☐	☐	☐	☐	0.260		P	☐	OK	☐	3 3/8	2 5/16	3 1/4	1.000	☐	OK	☐	3 3/8	6	1.000	P	OK
89	N/A	☐	☐	☐	☐	☐	☐	☐	☐	0.286		P	☐	OK	☐	3 3/8	2 5/16	5 1/4	1.000	☐	OK	☐	3 3/8	8 1/4	1.000	P	OK
90	N/A	☐	☐	☐	☐	☐	☐	☐	☐	0.276		P	☐	OK	☐	3 3/8	2 5/16	3 3/8	1.000	☐	OK	☐	3 3/8	6	1.000	P	OK
91	N/A	☐	☐	☐	☐	☐	☐	☐	☐	0.234		P	☐	OK	☐	3 3/8	2 5/16	3 3/8	1.000	☐	OK	☐	3 3/8	6 1/4	1.000	P	OK
92	N/A	☐	☐	☐	☐	☐	☐	☐	☐	0.262		P	☐	OK	☐	3 3/8	2 5/16	3 3/8	1.000	☐	OK	☐	3 3/8	6	1.000	P	OK
93	N/A	☐	☐	☐	☐	☐	☐	☐	☐	0.238		P	☐	OK	☐	3 3/8	2 5/16	3 1/4	1.000	☐	OK	☐	3 3/8	6	1.000	P	OK
94	N/A	☐	☐	☐	☐	☐	☐	☐	☐	0.266		P	☐	OK	☐	3 3/8	2 5/16	1 3/4	1.000	☐	OK	☐	3 3/8	3 5/16	1.000	P	OK
95	N/A	☐	☐	☐	☐	☐	☐	☐	☐	0.267		P	☐	OK	☐	3 3/8	2 5/16	3 1/4	1.000	☐	OK	☐	3 3/8	6 1/8	1.000	P	OK
96	N/A	☐	☐	☐	☐	☐	☐	☐	☐	0.266		P	☐	OK	☐	3 3/8	2 5/16	5	1.000	☐	OK	☐	3 3/8	7 3/4	1.000	P	OK
97	N/A	☐	☐	☐	☐	☐	☐	☐	☐	0.259		P	☐	OK	☐	3 3/8	2 3/8	3 3/8	1.000	☐	OK	☐	3 3/8	3 3/8	1.000	P	OK
98	N/A	☐	☐	☐	☐	☐	☐	☐	☐	0.246		P	☐	OK	☐	3 3/8	2 5/16	3 3/8	1.000	☐	OK	☐	3 3/8	6	1.000	P	OK
99	N/A	☐	☐	☐	☐	☐	☐	☐	☐	0.277		P	☐	OK	☐	3 3/8	2 5/16	3 1/4	1.000	☐	OK	☐	3 3/8	6	1.000	P	OK
100	N/A	☐	☐	☐	☐	☐	☐	☐	☐	0.277		P	☐	OK	☐	3 3/8	2 5/16	5 1/4	1.000	☐	OK	☐	3 3/8	8 1/8	1.000	P	OK



Date:	11/12/2025	-	11/12/2025	Rig Name:	N/A	Size:	2 7/8	Weight:	7.90	Nom. Wall:	0.248
Customer:				Inspected At:	Lead NDT Yard	Grade:	P-110	Connection:	PH-6	80% Wall:	0.198
Customer Order #:	N/A			Job Spec:	DS-1 WORKSTRINGS / API RP 7G	Range:	0.276	EMI Unit:	01	70% Wall:	0.174

CONNECTION DIMENSIONAL DATA CRITERIA											
PIN DIMENSIONS						BOX DIMENSIONS					
PIN LENGTH:	1.000	-	1.000	BEVEL DIAMETER:	1	BOX LENGTH:	1.000	-	1.000	C-BORE LENGTH:	1
MIN. O.D.:	3 5/16			PIN I.D.:	2 15/16	MIN. O.D.:	3 5/16			C-BORE DIAMETER:	1
MIN. SHDR. WIDTH:	1			MIN. TONG SPACE:	5/16	MIN. SHDR. WIDTH:	1			MIN. TONG SPACE:	3

JOINT NO.	SERIAL NO.	TUBE CONDITION											PIN CONDITION							BOX CONDITION						FINAL CLASS	COMMENTS
		DENTS/MASH	SLIP AREA	CUTS/GOUGES	O.D. WEAR	PITTING	CRACKED	COATING	CROOKED	MIN. WALL THICKNESS	MAX. WALL THICKNESS	CLASS	HARBAND	CONNECTION CLASS	REFACE	O.D.	I.D.	TONG SPACE	PIN LENGTH	HARBAND	CONNECTION CLASS	REFACE	O.D.	TONG SPACE	BOX LENGTH		
101	N/A	☐	☐	☐	☐	☐	☐	☐	☐	0.260		P	☐	OK	☐	3 3/8	2 5/16	5 3/8	1.000	☐	OK	☐	3 3/8	8 1/4	1.000	P	OK
102	N/A	☐	☐	☐	☐	☐	☐	☐	☐	0.261		P	☐	OK	☐	3 3/8	2 5/16	3 1/4	1.000	☐	OK	☐	3 3/8	6 1/4	1.000	P	OK
103	N/A	☐	☐	☐	☐	☐	☐	☐	☐	0.276		P	☐	OK	☐	3 3/8	2 5/16	3 1/8	1.000	☐	OK	☐	3 3/8	6	1.000	P	OK
104	N/A	☐	☐	☐	☐	☐	☐	☐	☐	0.270		P	☐	OK	☐	3 3/8	2 5/16	3 3/8	1.000	☐	OK	☐	3 3/8	6	1.000	P	OK
105	N/A	☐	☐	☐	☐	☐	☐	☐	☐	0.279		P	☐	OK	☐	3 3/8	2 5/16	5 1/4	1.000	☐	OK	☐	3 3/8	6 3/4	1.000	P	OK
106	N/A	☐	☐	☐	☐	☐	☐	☐	☐	0.265		P	☐	OK	☐	3 3/8	2 5/16	1 7/8	1.000	☐	OK	☐	3 3/8	6 1/4	1.000	P	OK
107	N/A	☐	☐	☐	☐	☐	☐	☐	☐	0.255		P	☐	OK	☐	3 3/8	2 3/8	6 1/4	1.000	☐	OK	☐	3 3/8	6 1/4	1.000	P	OK
108	N/A	☐	☐	☐	☐	☐	☐	☐	☐	0.249		P	☐	OK	☐	3 3/8	2 5/16	5 1/4	1.000	☐	OK	☐	3 3/8	7	1.000	P	OK
109	N/A	☐	☐	☐	☐	☐	☐	☐	☐	0.200		P	☐	OK	☐	3 3/8	2 3/8	3 1/8	1.000	☐	OK	☐	3 3/8	6 1/4	1.000	P	OK
110	N/A	☐	☐	☐	☐	☐	☐	☐	☐	0.282		P	☐	OK	☐	3 3/8	2 5/16	3 3/8	1.000	☐	OK	☐	3 3/8	6 1/4	1.000	P	OK
111	N/A	☐	☐	☐	☐	☐	☐	☐	☐	0.275		P	☐	OK	☐	3 3/8	2 5/16	3 1/8	1.000	☐	OK	☐	3 3/8	6 1/8	1.000	P	OK
112	N/A	☐	☐	☐	☐	☐	☐	☐	☐	0.295		P	☐	OK	☐	3 3/8	2 5/16	3 1/8	1.000	☐	OK	☐	3 3/8	6 1/4	1.000	P	OK
113	N/A	☐	☐	☐	☐	☐	☐	☐	☐	0.274		P	☐	OK	☐	3 3/8	2 5/16	5 1/4	1.000	☐	OK	☐	3 3/8	8 1/8	1.000	P	OK
114	N/A	☐	☐	☐	☐	☐	☐	☐	☐	0.276		P	☐	OK	☐	3 3/8	2 5/16	3 1/4	1.000	☐	OK	☐	3 3/8	6	1.000	P	OK
115	N/A	☐	☐	☐	☐	☐	☐	☐	☐	0.271		P	☐	OK	☐	3 3/8	2 5/16	3 1/4	1.000	☐	OK	☐	3 3/8	6 1/4	1.000	P	OK
116	N/A	☐	☐	☐	☐	☐	☐	☐	☐	0.209		P	☐	OK	☐	3 3/8	2 5/16	1 7/8	1.000	☐	OK	☐	3 3/8	5 1/2	1.000	P	OK
117	N/A	☐	☐	☐	☐	☐	☐	☐	☐	0.264		P	☐	OK	☐	3 3/8	2 5/16	3 1/4	1.000	☐	OK	☐	3 3/8	6 1/4	1.000	P	OK
118	N/A	☐	☐	☐	☐	☐	☐	☐	☐	0.262		P	☐	OK	☐	3 3/8	2 5/16	3 3/8	1.000	☐	OK	☐	3 3/8	6	1.000	P	OK
119	N/A	☐	☐	☐	☐	☐	☐	☐	☐	0.236		P	☐	OK	☐	3 3/8	2 5/16	5 1/4	1.000	☐	OK	☐	3 3/8	8	1.000	P	OK
120	N/A	☐	☐	☐	☐	☐	☐	☐	☐	0.221		P	☐	OK	☐	3 3/8	2 5/16	5 1/4	1.000	☐	OK	☐	3 3/8	8 1/4	1.000	P	OK



Date:	11/12/2025	-	11/12/2025	Rig Name:	N/A	Size:	2 7/8	Weight:	7.90	Nom. Wall:	0.248
Customer:				Inspected At:	Lead NDT Yard	Grade:	P-110	Connection:	PH-6	80% Wall:	0.198
Customer Order #:	N/A			Job Spec:	DS-1 WORKSTRINGS / API RP 7G	Range:	0.276	EMI Unit:	01	70% Wall:	0.174

CONNECTION DIMENSIONAL DATA CRITERIA											
PIN DIMENSIONS						BOX DIMENSIONS					
PIN LENGTH:	1.000	-	1.000	BEVEL DIAMETER:	1	BOX LENGTH:	1.000	-	1.000	C-BORE LENGTH:	1
MIN. O.D.:	3 5/16			PIN I.D.:	2 15/16	MIN. O.D.:	3 5/16			C-BORE DIAMETER:	1
MIN. SHDR. WIDTH:	1			MIN. TONG SPACE:	5/16	MIN. SHDR. WIDTH:	1			MIN. TONG SPACE:	3

JOINT NO.	SERIAL NO.	TUBE CONDITION											PIN CONDITION							BOX CONDITION						FINAL CLASS	COMMENTS
		DENTS/MASH	SLIP AREA	CUTS/GOUGES	O.D. WEAR	PITTING	CRACKED	COATING	CROOKED	MIN. WALL THICKNESS	MAX. WALL THICKNESS	CLASS	HARBAND	CONNECTION CLASS	REFACE	O.D.	I.D.	TONG SPACE	PIN LENGTH	HARBAND	CONNECTION CLASS	REFACE	O.D.	TONG SPACE	BOX LENGTH		
121	N/A	☐	☐	☐	☐	☐	☐	☐	☐	0.275		P	☐	OK	☐	3 3/8	2 5/16	3 1/4	1.000	☐	OK	☐	3 3/8	6 1/4	1.000	P	OK
122	N/A	☐	☐	☐	☐	☐	☐	☐	☐	0.270		P	☐	OK	☐	3 3/8	2 5/16	3 1/4	1.000	☐	OK	☐	3 3/8	6 1/4	1.000	P	OK
123	N/A	☐	☐	☐	☐	☐	☐	☐	☐	0.268		P	☐	OK	☐	3 3/8	2 5/16	3 1/4	1.000	☐	OK	☐	3 3/8	8	1.000	P	OK
124	N/A	☐	☐	☐	☐	☐	☐	☐	☐	0.245		P	☐	OK	☐	3 3/8	2 5/16	5 1/8	1.000	☐	OK	☐	3 3/8	6 1/8	1.000	P	OK
125	N/A	☐	☐	☐	☐	☐	☐	☐	☐	0.266		P	☐	OK	☐	3 3/8	2 5/16	3 1/4	1.000	☐	OK	☐	3 3/8	6	1.000	P	OK
126	N/A	☐	☐	☐	☐	☐	☐	☐	☐	0.256		P	☐	OK	☐	3 3/8	2 5/16	5 1/4	1.000	☐	OK	☐	3 3/8	8	1.000	P	OK
127	N/A	☐	☐	☐	☐	☐	☐	☐	☐	0.243		P	☐	OK	☐	3 3/8	2 5/16	1	1.000	☐	OK	☐	3 3/8	5	1.000	P	OK
128	N/A	☐	☐	☐	☐	☐	☐	☐	☐	0.266		P	☐	OK	☐	3 3/8	2 5/16	1 1/4	1.000	☐	OK	☐	3 3/8	3 3/4	1.000	P	OK
129	N/A	☐	☐	☐	☐	☐	☐	☐	☐	0.239		P	☐	OK	☐	3 3/8	2 5/16	5 1/4	1.000	☐	OK	☐	3 3/8	8 1/4	1.000	P	OK
130	N/A	☐	☐	☐	☐	☐	☐	☐	☐	0.239		P	☐	OK	☐	3 3/8	2 5/16	2 3/4	1.000	☐	OK	☐	3 3/8	5 3/4	1.000	P	OK
131	N/A	☐	☐	☐	☐	☐	☐	☐	☐	0.276		P	☐	OK	☐	3 3/8	2 5/16	3 1/2	1.000	☐	OK	☐	3 3/8	6	1.000	P	OK
132	N/A	☐	☐	☐	☐	☐	☐	☐	☐	0.258		P	☐	OK	☐	3 3/8	2 5/16	2	1.000	☐	OK	☐	3 3/8	6 3/8	1.000	P	OK
133	N/A	☐	☐	☐	☐	☐	☐	☐	☐	0.287		P	☐	OK	☐	3 3/8	2 5/16	5 1/4	1.000	☐	OK	☐	3 3/8	8	1.000	P	OK
134	N/A	☐	☐	☐	☐	☐	☐	☐	☐	0.266		P	☐	OK	☐	3 3/8	2 5/16	3 1/4	1.000	☐	OK	☐	3 3/8	6	1.000	P	OK
135	N/A	☐	☐	☐	☐	☐	☐	☐	☐	0.254		P	☐	OK	☐	3 3/8	2 5/16	5 1/4	1.000	☐	OK	☐	3 3/8	8	1.000	P	OK
136	N/A	☐	☐	☐	☐	☐	☐	☐	☐	0.236		P	☐	OK	☐	3 3/8	2 5/16	3 1/4	1.000	☐	OK	☐	3 3/8	6 1/4	1.000	P	OK
137	N/A	☐	☐	☐	☐	☐	☐	☐	☐	0.255		P	☐	OK	☐	3 3/8	2 5/16	1 1/4	1.000	☐	OK	☐	3 3/8	4	1.000	P	OK
138	N/A	☐	☐	☐	☐	☐	☐	☐	☐	0.288		P	☐	OK	☐	3 3/8	2 5/16	3 1/4	1.000	☐	OK	☐	3 3/8	6 1/4	1.000	P	OK
139	N/A	☐	☐	☐	☐	☐	☐	☐	☐	0.281		P	☐	OK	☐	3 3/8	2 5/16	3 1/4	1.000	☐	OK	☐	3 3/8	6	1.000	P	OK
140	N/A	☐	☐	☐	☐	☐	☐	☐	☐	0.279		P	☐	OK	☐	3 3/8	2 5/16	3 1/4	1.000	☐	OK	☐	3 3/8	6 1/4	1.000	P	OK



Date:	11/12/2025	-	11/12/2025	Rig Name:	N/A	Size:	2 7/8	Weight:	7.90	Nom. Wall:	0.248
Customer:				Inspected At:	Lead NDT Yard	Grade:	P-110	Connection:	PH-6	80% Wall:	0.198
Customer Order #:	N/A			Job Spec:	DS-1 WORKSTRINGS / API RP 7G	Range:	0.276	EMI Unit:	01	70% Wall:	0.174

CONNECTION DIMENSIONAL DATA CRITERIA											
PIN DIMENSIONS						BOX DIMENSIONS					
PIN LENGTH:	1.000	-	1.000	BEVEL DIAMETER:	1	BOX LENGTH:	1.000	-	1.000	C-BORE LENGTH:	1
MIN. O.D.:	3 5/16			PIN I.D.:	2 15/16	MIN. O.D.:	3 5/16			C-BORE DIAMETER:	1
MIN. SHDR. WIDTH:	1			MIN. TONG SPACE:	5/16	MIN. SHDR. WIDTH:	1			MIN. TONG SPACE:	3

JOINT NO.	SERIAL NO.	TUBE CONDITION											PIN CONDITION							BOX CONDITION						FINAL CLASS	COMMENTS	
		DENTS/MASH	SLIP AREA	CUTS/GOUGES	O.D. WEAR	PITTING	CRACKED	COATING	CROOKED	MIN. WALL THICKNESS	MAX. WALL THICKNESS	CLASS	HARDBAND	CONNECTION CLASS	REFACE	O.D.	I.D.	TONG SPACE	PIN LENGTH	HARDBAND	CONNECTION CLASS	REFACE	O.D.	TONG SPACE	BOX LENGTH			
141	N/A	☐	☐	☐	☐	☐	☐	☐	☐	0.279		P	☐	OK	☐	3 3/8	2 5/16	3 1/4	1.000	☐	OK	☐	3 3/8	6 1/4	1.000	P	OK	
142	N/A	☐	☐	☐	☐	☐	☐	☐	☐	0.249		P	☐	OK	☐	3 3/8	2 5/16	5	1.000	☐	OK	☐	3 3/8	8	1.000	P	OK	
143	N/A	☐	☐	☐	☐	☐	☐	☐	☐	0.233		P	☐	OK	☐	3 3/8	2 5/16	3 1/4	1.000	☐	OK	☐	3 3/8	6	1.000	P	OK	
144	N/A	☐	☐	☐	☐	☐	☐	☐	☐	0.243		P	☐	OK	☐	3 3/8	2 5/16	3 3/8	1.000	☐	OK	☐	3 3/8	6 1/4	1.000	P	OK	
145	N/A	☐	☐	☐	☐	☐	☐	☐	☐	0.255		P	☐	OK	☐	3 3/8	2 5/16	4	1.000	☐	OK	☐	3 3/8	8	1.000	P	OK	
146	N/A	☐	☐	☐	☐	☐	☐	☐	☐	0.251		P	☐	OK	☐	3 3/8	2 5/16	5 1/4	1.000	☐	OK	☐	3 3/8	8	1.000	P	OK	
147	N/A	☐	☐	☐	☐	☐	☐	☐	☐	0.236		P	☐	OK	☐	3 3/8	2 5/16	2	1.000	☐	OK	☐	3 3/8	6	1.000	P	OK	
148	N/A	☐	☐	☐	☐	☐	☐	☐	☐	0.258		P	☐	OK	☐	3 3/8	2 5/16	3 3/8	1.000	☐	OK	☐	3 3/8	6 1/4	1.000	P	OK	
149	N/A	☐	☐	☐	☐	☐	☐	☐	☐	0.266		P	☐	OK	☐	3 3/8	2 5/16	5 1/4	1.000	☐	OK	☐	3 3/8	8	1.000	P	OK	
150	N/A	☐	☐	☐	☐	☐	☐	☐	☐	0.248		P	☐	OK	☐	3 3/8	2 5/16	5 1/4	1.000	☐	OK	☐	3 3/8	6	1.000	P	OK	
151	N/A	☐	☐	☐	☐	☐	☐	☐	☐	0.245		P	☐	OK	☐	3 3/8	2 5/16	3 1/4	1.000	☐	OK	☐	3 3/8	8	1.000	P	OK	
152	N/A	☐	☐	☐	☐	☐	☐	☐	☐	0.266		P	☐	OK	☐	3 3/8	2 5/16	5 1/4	1.000	☐	OK	☐	3 3/8	6	1.000	P	OK	
153	N/A	☐	☐	☐	☐	☐	☐	☐	☐	0.234		P	☐	OK	☐	3 3/8	2 5/16	5 1/4	1.000	☐	OK	☐	3 3/8	3 3/4	1.000	P	OK	
154	N/A	☐	☐	☐	☐	☐	☐	☐	☐	0.270		P	☐	OK	☐	3 3/8	2 5/16	2 1/8	1.000	☐	OK	☐	3 3/8	6 1/8	1.000	P	OK	
155	N/A	☐	☐	☐	☐	☐	☐	☐	☐	0.279		P	☐	OK	☐	3 3/8	2 5/16	3 1/4	1.000	☐	OK	☐	3 3/8	6 1/4	1.000	P	OK	
156	N/A	☐	☐	☐	☐	☐	☐	☐	☐	0.254		P	☐	OK	☐	3 3/8	2 5/16	2	1.000	☐	OK	☐	3 3/8	6	1.000	P	OK	
157	N/A	☐	☐	☐	☐	☐	☐	☐	☐	0.278		P	☐	OK	☐	3 3/8	2 5/16	2	1.000	☐	OK	☐	3 3/8	6 1/8	1.000	P	OK	
158	N/A	☐	☐	☐	☐	☐	☐	☐	☐	0.280		P	☐	OK	☐	3 3/8	2 5/16	3 1/4	1.000	☐	OK	☐	3 3/8	6 1/4	1.000	P	OK	
159	N/A	☐	☐	☐	☐	☐	☐	☐	☐	0.253		P	☐	OK	☐	3 3/8	2 5/16	3 1/4	1.000	☐	OK	☐	3 3/8	8 1/4	1.000	P	OK	
160	N/A	☐	☐	☐	☐	☐	☐	☐	☐	0.293		P	☐	OK	☐	3 3/8	2 5/16	3 1/2	1.000	☐	OK	☐	3 3/8	6 1/8	1.000	P	OK	



Date:	11/12/2025	-	11/12/2025	Rig Name:	N/A	Size:	2 7/8	Weight:	7.90	Nom. Wall:	0.248
Customer:				Inspected At:	Lead NDT Yard	Grade:	P-110	Connection:	PH-6	80% Wall:	0.198
Customer Order #:	N/A			Job Spec:	DS-1 WORKSTRINGS / API RP 7G	Range:	0.276	EMI Unit:	01	70% Wall:	0.174

CONNECTION DIMENSIONAL DATA CRITERIA											
PIN DIMENSIONS						BOX DIMENSIONS					
PIN LENGTH:	1.000	-	1.000	BEVEL DIAMETER:	1	BOX LENGTH:	1.000	-	1.000	C-BORE LENGTH:	1
MIN. O.D.:	3 5/16			PIN I.D.:	2 15/16	MIN. O.D.:	3 5/16			C-BORE DIAMETER:	1
MIN. SHDR. WIDTH:	1			MIN. TONG SPACE:	5/16	MIN. SHDR. WIDTH:	1			MIN. TONG SPACE:	3

JOINT NO.	SERIAL NO.	TUBE CONDITION											PIN CONDITION							BOX CONDITION						FINAL CLASS	COMMENTS	
		DENTS/MASH	SLIP AREA	CUTS/GOUGES	O.D. WEAR	PITTING	CRACKED	COATING	CROOKED	MIN. WALL THICKNESS	MAX. WALL THICKNESS	CLASS	HARDBAND	CONNECTION CLASS	REFACE	O.D.	I.D.	TONG SPACE	PIN LENGTH	HARDBAND	CONNECTION CLASS	REFACE	O.D.	TONG SPACE	BOX LENGTH			
161	N/A	☐	☐	☐	☐	☐	☐	☐	☐	0.256		P	☐	OK	☐	3 3/8	2 5/16	3 1/2	1.000	☐	OK	☐	3 3/8	5	1.000	P	OK	
162	N/A	☐	☐	☐	☐	☐	☐	☐	☐	0.252		P	☐	OK	☐	3 3/8	2 5/16	3 3/8	1.000	☐	OK	☐	3 3/8	6	1.000	P	OK	
163	N/A	☐	☐	☐	☐	☐	☐	☐	☐	0.261		P	☐	OK	☐	3 3/8	2 5/16	3 1/4	1.000	☐	OK	☐	3 3/8	6 1/4	1.000	P	OK	
164	N/A	☐	☐	☐	☐	☐	☐	☐	☐	0.255		P	☐	OK	☐	3 3/8	2 5/16	3 3/8	1.000	☐	OK	☐	3 3/8	6 1/8	1.000	P	OK	
165	N/A	☐	☐	☐	☐	☐	☐	☐	☐	0.236		P	☐	OK	☐	3 3/8	2 5/16	3 3/8	1.000	☐	OK	☐	3 3/8	6 1/4	1.000	P	OK	
166	N/A	☐	☐	☐	☐	☐	☐	☐	☐	0.254		P	☐	OK	☐	3 3/8	2 5/16	2 1/8	1.000	☐	OK	☐	3 3/8	5	1.000	P	OK	
167	N/A	☐	☐	☐	☐	☐	☐	☐	☐	0.244		P	☐	OK	☐	3 3/8	2 5/16	4 1/8	1.000	☐	OK	☐	3 3/8	8 1/8	1.000	P	OK	
168	N/A	☐	☐	☐	☐	☐	☐	☐	☐	0.265		P	☐	OK	☐	3 3/8	2 5/16	3 1/4	1.000	☐	OK	☐	3 3/8	6 1/8	1.000	P	OK	
169	N/A	☐	☐	☐	☐	☐	☐	☐	☐	0.230		P	☐	OK	☐	3 3/8	2 5/16	4 1/8	1.000	☐	OK	☐	3 3/8	8 1/8	1.000	P	OK	
170	N/A	☐	☐	☐	☐	☐	☐	☐	☐	0.252		P	☐	OK	☐	3 3/8	2 5/16	3 3/8	1.000	☐	OK	☐	3 3/8	6 1/4	1.000	P	OK	
171	N/A	☐	☐	☐	☐	☐	☐	☐	☐	0.270		P	☐	OK	☐	3 3/8	2 5/16	3 3/8	1.000	☐	OK	☐	3 3/8	6	1.000	P	OK	
172	N/A	☐	☐	☐	☐	☐	☐	☐	☐	0.265		P	☐	OK	☐	3 3/8	2 5/16	3 1/4	1.000	☐	OK	☐	3 3/8	6 1/8	1.000	P	OK	
173	N/A	☐	☐	☐	☐	☐	☐	☐	☐	0.263		P	☐	OK	☐	3 3/8	2 5/16	3 1/2	1.000	☐	OK	☐	3 3/8	6 1/8	1.000	P	OK	
174	N/A	☐	☐	☐	☐	☐	☐	☐	☐	0.280		P	☐	OK	☐	3 3/8	2 5/16	3 3/8	1.000	☐	OK	☐	3 3/8	6 1/5	1.000	P	OK	
175	N/A	☐	☐	☐	☐	☐	☐	☐	☐	0.275		P	☐	OK	☐	3 3/8	2 5/16	3 1/4	1.000	☐	OK	☐	3 3/8	4 3/4	1.000	P	OK	
176	N/A	☐	☐	☐	☐	☐	☐	☐	☐	0.266		P	☐	OK	☐	3 3/8	2 5/16	3 1/4	1.000	☐	OK	☐	3 3/8	6 1/8	1.000	P	OK	
177	N/A	☐	☐	☐	☐	☐	☐	☐	☐	0.274		P	☐	OK	☐	3 3/8	2 5/16	3 1/4	1.000	☐	OK	☐	3 3/8	6 1/8	1.000	P	OK	
178	N/A	☐	☐	☐	☐	☐	☐	☐	☐	0.265		P	☐	OK	☐	3 3/8	2 5/16	3 3/8	1.000	☐	OK	☐	3 3/8	6	1.000	P	OK	
179	N/A	☐	☐	☐	☐	☐	☐	☐	☐	0.261		P	☐	OK	☐	3 3/8	2 5/16	3 3/8	1.000	☐	OK	☐	3 3/8	6 1/4	1.000	P	OK	
180	N/A	☐	☐	☐	☐	☐	☐	☐	☐	0.248		P	☐	OK	☐	3 3/8	2 5/16	5 1/4	1.000	☐	OK	☐	3 3/8	8	1.000	P	OK	



Date:	11/12/2025	-	11/12/2025	Rig Name:	N/A	Size:	2 7/8	Weight:	7.90	Nom. Wall:	0.248
Customer:				Inspected At:	Lead NDT Yard	Grade:	P-110	Connection:	PH-6	80% Wall:	0.198
Customer Order #:	N/A			Job Spec:	DS-1 WORKSTRINGS / API RP 7G	Range:	0.276	EMI Unit:	01	70% Wall:	0.174

CONNECTION DIMENSIONAL DATA CRITERIA

PIN DIMENSIONS				BOX DIMENSIONS					
PIN LENGTH:	1.000	-	1.000	BEVEL DIAMETER:	1	BOX LENGTH:	1.000 - 1.000	C-BORE LENGTH:	1
MIN. O.D.:	3 5/16			PIN I.D.:	2 15/16	MIN. O.D.:	3 5/16	C-BORE DIAMETER:	1
MIN. SHDR. WIDTH:	1			MIN. TONG SPACE:	5/16	MIN. SHDR. WIDTH:	1	MIN. TONG SPACE:	3

JOINT NO.	SERIAL NO.	TUBE CONDITION											PIN CONDITION							BOX CONDITION						FINAL CLASS	COMMENTS
		DENTS/MASH	SLIP AREA	CUTS/GOUGES	O.D. WEAR	PITTING	CRACKED	COATING	CROOKED	MIN. WALL THICKNESS	MAX. WALL THICKNESS	CLASS	HARDBAND	CONNECTION CLASS	REFACE	O.D.	I.D.	TONG SPACE	PIN LENGTH	HARDBAND	CONNECTION CLASS	REFACE	O.D.	TONG SPACE	BOX LENGTH		
181	N/A	☐	☐	☐	☐	☐	☐	☐	☐	0.234		P	☐	OK	☐	3 3/8	2 5/16	3 1/4	1.000	☐	OK	☐	3 3/8	6 1/8	1.000	P	OK
182	N/A	☐	☐	☐	☐	☐	☐	☐	☐	0.245		P	☐	OK	☐	3 3/8	2 5/16	1 3/8	1.000	☐	OK	☐	3 3/8	5 5/8	1.000	P	OK
183	N/A	☐	☐	☐	☐	☐	☐	☐	☐	0.265		P	☐	OK	☐	3 3/8	2 5/16	3 1/8	1.000	☐	OK	☐	3 3/8	6	1.000	P	OK
184	N/A	☐	☐	☐	☐	☐	☐	☐	☐	0.252		P	☐	OK	☐	3 3/8	2 5/16	5 1/4	1.000	☐	OK	☐	3 3/8	8 1/8	1.000	P	OK
185	N/A	☐	☐	☐	☐	☐	☐	☐	☐	0.269		P	☐	OK	☐	3 3/8	2 5/16	2	1.000	☐	OK	☐	3 3/8	6 1/8	1.000	P	OK
		☐	☐	☐	☐	☐	☐	☐	☐				☐		☐					☐		☐					
		☐	☐	☐	☐	☐	☐	☐	☐				☐		☐					☐		☐					
		☐	☐	☐	☐	☐	☐	☐	☐				☐		☐					☐		☐					
		☐	☐	☐	☐	☐	☐	☐	☐				☐		☐					☐		☐					
		☐	☐	☐	☐	☐	☐	☐	☐				☐		☐					☐		☐					
		☐	☐	☐	☐	☐	☐	☐	☐				☐		☐					☐		☐					
		☐	☐	☐	☐	☐	☐	☐	☐				☐		☐					☐		☐					
		☐	☐	☐	☐	☐	☐	☐	☐				☐		☐					☐		☐					
		☐	☐	☐	☐	☐	☐	☐	☐				☐		☐					☐		☐					
		☐	☐	☐	☐	☐	☐	☐	☐				☐		☐					☐		☐					
		☐	☐	☐	☐	☐	☐	☐	☐				☐		☐					☐		☐					
		☐	☐	☐	☐	☐	☐	☐	☐				☐		☐					☐		☐					
		☐	☐	☐	☐	☐	☐	☐	☐				☐		☐					☐		☐					
		☐	☐	☐	☐	☐	☐	☐	☐				☐		☐					☐		☐					
		☐	☐	☐	☐	☐	☐	☐	☐				☐		☐					☐		☐					